





Stump Grinders

### TECHNICAL SPECIFICATIONS

DESCRIPTION	TRACTOR MODEL	MOBILE VERSION
Power requirements	45 to 70 kw (@1000 RPM PTO	100 to 118kw Deutz Power
Maximum operating pressure	350 Bar	400 Bar.
Volume in reservoir	120 liter Hydraulic Oil	225 Litre hydraulic Oil/180 litre Fuel
Dimensions: <ul style="list-style-type: none"> <li>• Height</li> <li>• Width</li> <li>• Length</li> <li>• Weight</li> </ul>	1.30 meter 1.50 meter 2.10 meter 696 kg	2.45 meter 2.48 meter 5.50 meter 3215 Kg

### OPERATING SPECIFICATIONS

DESCRIPTION	TRACTOR MODEL	MOBILE VERSION
Maximum cut per slew	14 cm	17.5 cm
Maximum stump height	100 cm	150 cm
Maximum width per slew	1.02 m	1.20 m
Maximum depth	40 cm	50 cm

### FEATURES

- \* Cut on left and right slew
- \* Automatic freewheel on cutter disc enabling instant engaging of tractor gears
- \* Also no power wasted to speed up cutting wheel on moving to next stump
- \* Tungsten carbide cutters easily replaced by operator as required
- \* Rugged heavy duty cutting wheel gives hours of maintenance free operation
- \* Drives off a standard 540 or 1000 RPM power take off depending on tractor kw
- \* **Cutting disc rotation can be reversed for confined areas..**

Specifications are subject to change without notice  
 Send email to [info@bellaco-stumpgrinders.com](mailto:info@bellaco-stumpgrinders.com) for latest version